

SPHYNX52

LED bar Driving light SLIM LED bar 52 cm with Dual (amber+white) position light



This new, slender 40 mm LEDBAR has already set high standards at its introduction. A beautiful design in which a 'black-vision' reflector was integrated gives a very exclusive look. The light output is absolutely phenomenal. You can easily switch between white or orange position light. Thanks to the 3 different lengths you can choose the best suited device to install on or in your vehicle. With the waterproof connector, a perfect connection is 100% guaranteed.



Has a DUAL position function (white & amber)

Specifications

Color	White
Operating voltage	12V - 24V
Mounting	Bolt M8
Type	Driving light LED bar
Operation temperature	-40° C / +60°C
Light source	LED
Length of cable (meter)	0,45 m
Current draw 12V Amp	6,2 Amp
Current draw 24V Amp	2.6 Amp
Colour of lens	Clear
Connection	Deutsch connector
Mounting side	Usually placed in front
Lumen	8100
Raw Lumen	9600
Reference mark	50
Kelvin value	6000K
Dimensions	520 x 40.5 x 52.5 mm
Length mm	520 mm
Certification	ECE R112+R7

SPHYNX52

LED bar Driving light SLIM LED bar 52 cm with Dual (amber+white) position light

EMC R10	Yes
EMC	EMC R10
IP-degree	IP66+IP68
To be ordered by	1
Packing	POS packaging
Specifications	210000 candela
EAN	5414184005624

